

sergé

sergé

sergé



roller

Composition: 42% Glass / 58% PVC

Width: 3200mm

Weight: 525gsm

Openness: 3%


Thickness: 0.83mm

Colour Fastness: 7-8


Fire Rating: M1 NF P92-503

Solar Optical Properties: Below

complete colour palette




grey white
(front/back)




grey



linen white
(front/back)




black linen
(front/back)



grey black
(front/back)



black




pitch black 5%



bronze



pearl



linen



black bronze
(front/back)



grey 1%



grey black 1%
front/back



black grey 1%
(front/back)



black 1%

	Ts	Rs	As	Tv	Tuv
Grey White (Front)	4.4	27.2	68.4	4.4	3.0
Grey White (Back)	4.4	38.9	56.7	4.4	3.0
Grey	5.1	14.2	80.7	4.9	4.8
Linen White (Front)	15.2	56.8	28.0	13.5	4.2
Linen White (Back)	15.2	58.9	25.9	13.5	4.2
Black Linen (Front)	5.6	16.1	78.3	5.3	4.0
Black Linen (Back)	5.6	26.0	68.4	5.3	4.0
Grey Black (Front)	3.7	12.7	83.6	3.7	3.6
Grey Black (Back)	3.7	9.6	86.7	3.7	3.6
Black	2.6	5.2	92.2	2.6	2.6
Pitch Black 5%	6	3	91	6	5.9
Bronze	4.8	9.1	86.1	4.7	4.8
Pearl	7.7	39.7	52.6	6	3.8
Linen	13.4	53.2	33.4	11	4.2
Black Bronze (Front)	6.0	5.8	88.2	5.8	5.8
Black Bronze (Back)	6.0	6.2	87.9	5.8	5.8
Grey 1%	4.8	21.6	73.6	2.2	0.9
Grey Black 1% (Front)	2.9	16.0	81.1	1.5	0.6
Grey Black 1% (Back)	2.9	16.0	81.1	1.5	0.6
Black Grey 1% (Front)	0.8	10.2	89.0	0.6	0.5
Black Grey 1% (Back)	0.8	10.1	89.1	0.6	0.5
Black 1%	0.4	6.69	92.9	0.3	0.3

Ts - Solar Transmittance
Rs - Solar Reflectance
As - Solar Absorbance
Tv - Visual Transmittance
Tuv - UV Transmittance

N.B. - Colours may vary from the digital representation.